







## Uninterruptible Power Systems (UPS): 320 VA up to 3000 VA

Part #	Va/Watts Rating	Voltage/HZ (IN/OUT)	Runtime - min. (Full/Half Load)	Output Receptable(s)	Input Connection	Technology	Cost	
<b>SDU Series Off-Line UPS:</b> Din Rail mount for panel applications								
<i>Handles 2 of the 9 common power conditions (Blackouts - Surge)</i>							<b>Good</b>	<b>\$\$</b>
	<b>SDU500</b>	500VA/310W	120, 50/60Hz	4 Min full load	Hardwire	Hardwire	OFFLINE	
	<b>SDU850</b>	850VA/510W	120, 50/60Hz	2 Min full load	Hardwire	Hardwire	OFFLINE	
* Add -5 suffix to part # for 230V model								
<b>S1K Series Off-Line UPS:</b> Recommended for OEM applications								
<i>Handles 3 of the 9 common power conditions (Blackouts - Sag - Surge)</i>							<b>Good</b>	<b>\$</b>
	<b>S1K320 **</b>	320VA/240W	115V, 50/60 Hz	10 Min. *		NEMA 5-15P		
	<b>S1K520 **</b>	520VA/340W	115V, 50/60 Hz	15 Min. *		NEMA 5-15P		
	<b>S1K650</b>	650VA/390W	115V, 50/60 Hz	15 Min. *	4 NEMA 5-15R outlets (3 Backed Up, 1 Surge only)	NEMA 5-15P	OFFLINE	
	<b>S1K850</b>	850VA/600W	115V, 50/60 Hz	25 Min. *		NEMA 5-15P	OFFLINE	
	<b>S1K1200</b>	1200VA/720W	115V, 50/60 Hz	30 Min. *		NEMA 5-15P		
	<b>S1K1500</b>	1500VA/900W	115V, 50/60 Hz	70 Min.*	4 NEMA 5-15R outlets (4 Backed Up)	NEMA 5-15P		
**AVR protection	<b>S1K-PMBRK</b>			* For a typical PC with a 15" monitor.	Wall/panel mount bracket			
<b>S2K Series Line-Interactive UPS:</b> Recommended for MRO applications								
<i>Handles 7 of the 9 common power conditions (Blackouts - Surge - Sags - Spike - Frequency Variations - Over and Under Voltages)</i>							<b>Better</b>	<b>\$\$</b>
	<b>S2K350</b>	350VA/210W	110/120/127, 50/60 Hz	8/26	(6) NEMA 5-15R	NEMA 5-15P		
	<b>S2K500</b>	500VA/300W	110/120/127, 50/60 Hz	8/24	(6) NEMA 5-15R	NEMA 5-15P	LINE	
	<b>S2K650</b>	650VA/390W	110/120/127, 50/60 Hz	5/16	(6) NEMA 5-15R	NEMA 5-15P	INTERACTIVE	
	<b>S2K1000</b>	1000VA/600W	110/120/127, 50/60 Hz	5/18	(6) NEMA 5-15R	NEMA 5-15P		
<b>S3K Series Mini-Tower Line-Interactive UPS:</b> Recommended for OEM applications								
<i>Handles 7 of the 9 common power conditions (Blackouts - Surge - Sags - Spike - Frequency Variations - Over and Under Voltages)</i>							<b>Better</b>	<b>\$\$</b>
	<b>S3K700</b>	700VA/480W	120V, 50/60 Hz	5/14	(4) NEMA 5-15R	NEMA 5-15P	LINE	
	<b>S3K1000</b>	1000VA/750W	120V, 50/60 Hz	4/13	(4) NEMA 5-15R	NEMA 5-15P	INTERACTIVE	
	<b>S3K1600</b>	1440VA/1200W	120V, 50/60 Hz	3/10	(4) NEMA 5-15R	NEMA 5-15P		
<b>S3K2U Series Rack/Tower Line-Interactive UPS:</b> Recommended for MRO & OEM applications								
<i>Handles 7 of the 9 common power conditions (Blackouts - Surge - Sags - Spike - Frequency Variations - Over and Under Voltages)</i>							<b>Better</b>	<b>\$\$\$</b>
	<b>S3K2U1000</b>	1000VA/750W	120V, 50/60 Hz	11/26	(8) NEMA 5-15R	NEMA 5-15P		
	<b>S3K2U1440</b>	1440VA/1080W	120V, 50/60 Hz	5/16	(8) NEMA 5-15R	NEMA 5-15P		
	<b>S3K2U2200</b>	2200VA/1650W	120V, 50/60 Hz	5/16	(6) NEMA 5-15R (2) NEMA 5-20R	NEMA L5-30P	LINE	
	<b>S3K2U1000-5</b>	1000VA/750W	230V, 50/60 Hz	11/26	(8) C13	IEC 320 (1) C14 INLET	INTERACTIVE	
	<b>S3K2U1440-5</b>	1440VA/1080W	230V, 50/60 Hz	5/16	(8) C13	IEC 320 (1) C14 INLET		
	<b>S3K2U2200-5</b>	2200VA/1650W	230V, 50/60 Hz	5/16	(8) C13, (1) C19	IEC 320 (1) C20 INLET		
	<b>S3K48BAT</b>	<b>S3K72BAT</b>	Battery cabinet to UPS interconnect cable provided.					
<b>S4K2U Industrial Online UPS:</b> Recommended for MRO & OEM applications ( <i>Hard wire option included with unit</i> )								
<i>Handles 9 of the 9 common power conditions (Blackouts - Frequency Variations - Surge - Sags - Spike - Extended Over Voltage - Noise - Harmonics)</i>							<b>BEST</b>	<b>\$\$\$\$</b>
	<b>S4K2U700</b>	700Va/490W	120V, 50/60 Hz	17/44	(4) NEMA 5-15R	NEMA 5-15P		
	<b>S4K2U1000</b>	1000VA/700W	120V, 50/60 Hz	11/25	(4) NEMA 5-15R	NEMA 5-15P	ON-LINE	
	<b>S4K2U1500</b>	1500VA/105W	120V, 50/60 Hz	7/20	(4) NEMA 5-15R	NEMA 5-15P	DOUBLE	
	<b>S4K2U2000</b>	2000VA/140W	120V, 50/60 Hz	6/14	(4) NEMA 5-15R (15/20 amp type)	NEMA 5-20P	CONVERSION	
	<b>S4K2U3000</b>	3000VA/2100W	120V, 50/60 Hz	5/16	(4) NEMA 5-15R (15/20 amp type)	NEMA L5-30P		
	<b>S4K2U48BAT</b>	<b>S4K2U96BAT</b>	External Battery Cabinet (provides extended run time)					